


ицию можно на сайт


XY13

# PIEZO CERAMIC TRANSDUCER

DIMENSIONS Unit:mm



## FREQUENCY RESPONSE



## SPECIFICATIONS


Type	XY13
Rated Voltage (V <sub>ip</sub> , Square Wave)	5
Operating Voltage (V <sub>op</sub> )	1-30
Rated Current (mA)	≤ 1
Capacitance at 120Hz (pF)	12000±30%
Sound Output at 40Hz, 10cm (dB)	≥ 70
Resonant Frequency (Hz)	4000±500
Operating Temperature (°C)	-20~+75
Storage Temperature (°C)	-30~+75
Weight (g)	1

● Values applying at rated voltage.


XY14



DIMENSIONS Unit:mm



## FREQUENCY RESPONSE



## SPECIFICATIONS

Type	XY14
Rated Voltage (V <sub>ip</sub> , Square Wave)	5
Operating Voltage (V <sub>op</sub> )	1-20
Rated Current (mA)	≤ 1
Capacitance at 120Hz (pF)	15000±30%
Sound Output at 4000Hz, 10cm (dB)	≥ 80
Resonant Frequency (Hz)	4000±500
Operating Temperature (°C)	-20~+75
Storage Temperature (°C)	-30~+75

● Values applying at rated voltage.

авьте заявку на почту