



70 MHz SAW Filter
Part Number 271252B

1. Features

- Typical 1dB bandwidth of 11.65 MHz
- Low-Loss Filter
- Single Ended Operation
- Surface Mounted Package (SMD)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications


Source and Load Impedance = 50

Room Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	70.0	-
Insertion Loss	dB	-	11.0	13.0
1dB Bandwidth	MHz	11.3	11.65	-
3dB Bandwidth	MHz	-	12.25	-
40dB Bandwidth	MHz	-	15.2	15.5
Amplitude Ripple (fo ± 5.5 MHz)	dB	-	0.45	1.0
Group Delay Variation (fo ± 5.5 MHz)	nsec	-	60	120
Absolute Delay	usec	-	1.3	-
Ultimate Rejection	dB	40	45	-
Temperature Coefficient of Frequency	ppm/°C	-	-86	-

S1365 Package Dimension



Matching Schematic



L1 = 120nH, C1 = 300pF, L2 = 82nH, C2 = 110pF

Pin Configuration

Pin Configuration			
Input	11	Ground	6, 12
Output	5	Others	Ground

Dimensions shown are nominal in millimeters

Body : Al₂O₃

Lid : Kovar, Ni Plated

Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating



70 MHz SAW Filter

Part Number 271252B

3. Typical Performance (at +25)

