Купить данную позицию можно на сайте: https://kvarci.ru/

IHD 好达 **SHOULDER**

石英晶体谐振器
QUARTZ CRYSTAL RESONATOR

HC-49S DIP



Features

- Resistance welded type crystal units.
- A great number of standard frequencies .
- High frequency pullability and low equivalent series resistance.
- Lower cost and highly mass production capacity.
- The best choice of PC, STB, LCDM, and Cable Modem.
- RoHS Compliant / Pb Free.

Electrical Specifications

Frequency Range	3.00 ~ 100.00 MHz
Load Capacitance	Series、6~32 pF、 or specify
Frequency Tolerance (at 25 ℃)	±10、±20、±30 ppm、 or specify
Frequency Stability Over Operating Temperature Range	±10、±20、±30 ppm、 or specify
Operating Temperature Range	-20 ~ +70 ℃、-40~+85 ℃、or specify
Storage Temperature Range	-40 ~ +85 ℃
Shunt Capacitance (C0)	7 pF Max.
Drive Level	1 ~ 1000 μW (100 μW typical)
Insulation Resistance	500 MΩ Minimum at 100VDC
Aging (at 25℃)	±3 ppm / year Max.

Equivalent Series Resistance(ESR)

Frequency Range (MHz)	Mode	ESRΩ(MAX)
3.00~3.49	FUND	150
3.50~3.99	FUND	120
4.00~4.99	FUND	100
5.00~6.99	FUND	80
7.00~7.99	FUND	70
8.00~8.99	FUND	60
9.00~9.99	FUND	50
10.00~10.99	FUND	40
11.00~19.99	FUND	30
20.00~40.00	FUND	25
27.00~29.99	3RD	100
30.00~44.99	3RD	80
45.00~80.00	3RD	60

Frequency Stability Over Operating Temperature Range

Temperature Range	Frequency Stability (ppm)						
	±3	±5	±7.5	±10	±15	±20	±30
0~+50℃	*	*	*	*	*	*	*
-10~+60℃		*	*	*	*	*	*
-20~+70℃			*	*	*	*	*
-30~+80℃				*	*	*	*
-40~+85℃					*	*	*

Dimensions



unit:mm

		TYPE	H MAX
L	13.2±0.5	49S	3.5
	20.0±0.5	49S2	2.7
	specify	49S3	2.5
		49S4	2.2

Для заказа отправьте заявку на почту: mail@kvarci.ru