

## CRYSTAL OSCILLATOR (SPXO)

OUTPUT : LV-PECL, LVDS

# SG3225EAN / VAN SG5032EAN / VAN SG7050EAN / VAN

- Achieved wide frequency range by PLL technology and AT crystal units
- Frequency range : 73.5 MHz to 700 MHz
- Supply voltage : 2.5 V to 3.3 V
- Function : Output enable (OE)
- Output : LV-PECL or LVDS

Product Number (please contact us)

SG3225EAN: X1G004251xxxx00

SG3225VAN: X1G004241xxxx00

SG5032EAN: X1G004271xxxx00

SG5032VAN: X1G004261xxxx00

SG7050EAN: X1G004291xxxx00

SG7050VAN: X1G004281xxxx00



SG3225EAN/VAN  
(3.2 × 2.5 × 1.05 mm)  
Actual size



SG5032EAN/VAN  
(5.0 × 3.2 × 1.0 mm)



SG7050EAN/VAN  
(7.0 × 5.0 × 1.4 mm)

SG3225EAN/VAN

SG5032EAN/VAN

SG7050EAN/VAN

## Specifications (characteristics)

Item	Symbol	Specifications		Conditions / Remarks	
		LV-PECL	LVDS		
		SG3225EAN / SG5032EAN / SG7050EAN	SG3225VAN / SG5032VAN / SG7050VAN		
Output frequency range	f <sub>0</sub>	73.5 MHz to 700 MHz		Please contact us about available frequencies.	
Supply voltage	V <sub>cc</sub>	K: 2.5 V - 10 % to 3.3 V + 10 %			
Storage temperature	T <sub>stg</sub>	-40 °C to +125 °C		Storage as single product.	
Operating temperature	T <sub>use</sub>	B: -20 °C to +70 °C, G: -40 °C to +85 °C			
Frequency tolerance	f <sub>tol</sub>	J: ± 50 × 10 <sup>-6</sup> , E: ± 30 × 10 <sup>-6</sup> , C: ± 20 × 10 <sup>-6</sup>			
Current consumption	I <sub>cc</sub>	65 mA Max.	30 mA Max.	OE = V <sub>cc</sub> , L <sub>ECL</sub> = 50 Ω or L <sub>LVDS</sub> = 100 Ω	
Disable current	I <sub>dis</sub>	20 mA Max.		OE = GND	
Symmetry	SYM	45 % to 55 %		At outputs crossing point	
Output voltage (LV-PECL)	V <sub>OH</sub>	V <sub>cc</sub> - 1.0 V to V <sub>cc</sub> - 0.8 V	-	DC characteristics	
	V <sub>OL</sub>	V <sub>cc</sub> - 1.78 V to V <sub>cc</sub> - 1.62 V	-		
Output voltage (LVDS)	V <sub>OD</sub>	-	250 mV to 450 mV	V <sub>OD1</sub> , V <sub>OD2</sub>	DC characteristics
	dV <sub>OD</sub>	-	50 mV Max.	dV <sub>OD</sub> =   V <sub>OD1</sub> -V <sub>OD2</sub>	
	V <sub>OS</sub>	-	1.15 V to 1.35 V	V <sub>OS1</sub> , V <sub>OS2</sub>	
	dV <sub>OS</sub>	-	150 mV Max.	dV <sub>OS</sub> =   V <sub>OS1</sub> -V <sub>OS2</sub>	
Output load condition (ECL) / (LVDS)	L <sub>ECL</sub>	50 Ω	-	Terminated to V <sub>cc</sub> -2.0 V	
	L <sub>LVDS</sub>	-	100 Ω	Connected between OUT to $\overline{\text{OUT}}$	
Input voltage	V <sub>IH</sub>	70 % V <sub>cc</sub> Min.		OE terminal	
	V <sub>IL</sub>	30 % V <sub>cc</sub> Max.			
Rise time / Fall time	t <sub>r</sub> / t <sub>f</sub>	350 ps Max.	300 ps Max.	LV-PECL: Between 20 % and 80 % of (V <sub>OH</sub> -V <sub>OL</sub> ). LVDS: Between 20 % and 80 % of Differential Output peak to peak voltage	
Start-up time	t <sub>str</sub>	3 ms Max.		Time at minimum supply voltage to be 0 s	
Phase Jitter	t <sub>PJ</sub>	0.6 ps Max.* <sup>1</sup>		Offset frequency: 12 kHz to 20 MHz	
Frequency aging	f <sub>aging</sub>	± 5 × 10 <sup>-6</sup> / year Max.		+25 °C, First year, V <sub>cc</sub> = 2.5 V, 3.3 V	

\*1 0.9 ps Max. (f<sub>o</sub> = 243 MHz ~ 250 MHz, 486 MHz ~ 500 MHz)

Product Name SG3225 E AN 156.250000MHz K J G A (CG is not available)

(Standard form)

Model Output (E: LV-PECL, V: LVDS) Frequency Supply voltage Frequency tolerance  
Operating temperature Internal identification code ("A" is default)


Supply voltage	
K	2.5 V ~ 3.3 V

Frequency tolerance	
J	±50 × 10 <sup>-6</sup>
E	±30 × 10 <sup>-6</sup>
C	±20 × 10 <sup>-6</sup>

Operating temperature	
B	-20 °C ~ +70 °C
G	-40 °C ~ +85 °C


## External dimensions

(Unit: mm)



## Footprint (Recommended)

(Unit: mm)



To maintain stable operation, provide a 0.01 μF to 0.1 μF by-pass capacitor at a location as near as possible to the power source terminal of the crystal product (between V<sub>cc</sub> - GND).

## PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.



## WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

### ► Explanation of the mark that are using it for the catalog

	► Pb free.
	► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc ).

## Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied data, circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of customer damage or infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
  - / Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.