

Oscillator · JCO · 3.3 V

Pin Type Oscillator

- soldering temperature: 260 °C max.
- metal package



General Data

type	JCO8 / JCO14 3.3 V
frequency range	1.0 ~ 160.0 MHz (15pF max.) 1.0 ~ 50.00 MHz (15pF~30pF max.)
frequency stability over all	± 15ppm ~ ± 100ppm (table 1)
current consumption	see table 2
supply voltage V_{DC}	3.3 V ± 10%
temperature	operating: -10 °C ~ +70 °C / -40 °C ~ +85 °C storage: -55 °C ~ +125 °C
output	rise & fall time: see table 3 load max: 15pF / 30pF current max.: 8mA low level max.: +0.5 V high level min.: $V_{DC} - 0.5 V$
output enable time max.	10ms
output disable time max.	100ns
start-up time max.	10ms
standby function	optional
phase jitter 12 kHz ~ 20.0 MHz	< 1.0ps RMS
symmetry at 0.5 x V_{DC}	45% ~ 55% typ. (40% ~ 60% max.)

Table 1: Frequency Stability Code

stability code	A	B	G	C	D	E
	± 100 ppm	± 50 ppm	± 30 ppm	± 25 ppm	± 20 ppm	± 15 ppm
-10 °C ~ +70 °C	○	●	○	○	○	○
-40 °C ~ +85 °C	●	○	○	○		
● standard ○ on request						

Table 2: Current Consumption max.

Current at 15pF load:	Current at 30pF load:
1.0 ~ 29.9 MHz 10 mA	1.0 ~ 29.9 MHz 20 mA
30.0 ~ 49.9 MHz 15 mA	30.0 ~ 50.0 MHz 35 mA
50.0 ~ 89.9 MHz 30 mA	
90.0 ~ 124.9 MHz 45 mA	
125.0 ~ 160.0 MHz 60 mA	

Table 3: Rise & Fall Time max.

6.0 ns: 1.0 ~ 49.9 MHz	note: - specific data on request - rise time: $0.1 V_{DC} \sim 0.9 V_{DC}$ - fall time: $0.9 V_{DC} \sim 0.1 V_{DC}$
5.0 ns: 50.0 ~ 79.9 MHz	
4.0 ns: 80.0 ~ 99.9 MHz	
3.0 ns: 100.0 ~ 160.0 MHz	

Dimensions JCO14 / JCO8

JCO14 	pin connection # 1: not connected or e/d # 7: ground # 8: output #14: supply voltage
JCO8 	pin connection # 1: not connected or e/d # 4: ground # 5: output # 8: supply voltage

Order Information

0	frequency	type	e/d function	frequency stability	supply voltage code	option
Oscillator	1.0 ~ 160.0 MHz	JCO8 JCO14	2 = no 3 = yes/tristate	see table 1	3.3 V = 3.3 Volt	blank = -10 °C ~ +70 °C T1 = -40 °C ~ +85 °C
Example: O 20.0-JCO8-3-A-3.3V-T1 (LF = RoHS compliant / Pb free pins or pads)						



Jauch Quartz GmbH • e-mail: info@jauch.de
 full data can be found under: www.jauch.de / www.jauch.fr / www.jauchusa.com

Для заказа отправьте заявку на почту: mail@kvarci.ru

Oscillator · JCO · 3.3 V


Enable / Disable Function

pin #1	pin #3
open or high	oscillation
gnd or low	high impedance

Marking

type
frequency
company code / date code

Wave Soldering Profile



Preferred Type

JC08-3-B-3.3
JC014-3-B-3.3

Packaging

JC08-3-B packed in antistatic plastic tubes, 40 pcs
JC014-3-B packed in antistatic plastic tubes, 25 pcs